

Polishing, Resurfacing, Stripping, Sanding



The **M2 HD Polisher** is built for high productivity in the harshest jobs like natural stone polishing, concrete resurfacing, wood screening and sanding. We fit the powerful 1.5 HP, 180 frame TEFC AC motor with 11:1 gears and industrial grade steel coupler. You will power your **M2** without blowing breakers and reducing down time. The 100% steel construction is accented with three exterior decorations.

Power

- 1.5 HP, 180 frame, TEFC AC motor
- 115-230 V, 60 Hz, (50 Hz optional)
- 50 ft., (12-3) 2-piece industrial power cord with cord lock **Drive System**

System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler, driving brushes at 165 RPM

Design

- All steel welded construction
- Steel brush covers with full wraparound bumper
- One piece heavy-duty steel handle with variable position lock
- Dual steel operating triggers with negative pressure on/off switch
- Thumb-operated safety switch
- Comfortable vinyl-dipped foam handle grips
- 1" x 5" non-marking ball bearing wheels
- 4 gallon solution tank
- 50 lb. Removable horseshoe weights (**optional**)

Safety

- Quiet 66 dB operation. Meets GS42 standard
- UL/CUL Listed



Product of US



Machine Size	Specifications			
	13"	15"	17"	20"
Model	M2-13	M2-15	M2-17	M2-20
Item #	F33-01-B	F35-01-B	F37-01-B	F40-01-B
Motor Cover	Black	Black	Black	Black
Brush Cover	Powder-Coated	Powder-Coated	Powder-Coated	Powder-Coated
Weight Machine	113 lbs.	117 lbs.	123 lbs.	125 lbs
All Sizes				
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC			
Pad Speed	165 RPM			
Power	115-230V, 60 Hz power. (50 Hz optional)			
Power Cord	50 ft., (12-3) industrial with cord lock			
Drive Gears	Triple-planetary XHD 11:1 helical-cut industrial			
Sound Level	66 dB - Meets GS42 standard			

Subject to change without notice



Optional Dust Pickup System with Vacuum Connection



50 lbs. Removable Weight Kit



Use with Cheetah Pad System



Use with Monkey Pad System